



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

**Gummi-Metall-Puffer**

**Ausführung 1**


beidseitig Außengewinde

Shore A Härte 55° +/-5°

Metall-Werkstoff: Stahl

Oberfläche: Blau verzinkt 8-12 µ / RoHS konform

Toleranz: DIN ISO 3302-1 Klasse M 3



Artikel	Durchmesser D mm	Höhe H mm	Gewinde G	Gewindelänge L mm	Gewindetiefe T mm
08 – 08 – 1	8	8	M 3	6	
12,5 – 12,5 – 1	12,5	12,5	M 5	12,5	
12,5 – 19,0 – 1	12,5	19	M 5	12,5	
10 – 08 – 1	10	8	M 4	10	
10 – 10 – 1	10	10	M 4	10	
10 – 15 – 1	10	15	M 4	10	
15 – 06 – 1	15	6	M 4	10	
15 – 07 – 1	15	7	M 4	10	
15 – 08 – 1	15	8	M 4	10	
15 – 10 – 1	15	10	M 4	10	
15 – 15 – 1	15	15	M 4	10	
15 – 20 – 1	15	20	M 4	10	
15 – 25 – 1	15	25	M 4	10	
15 – 10 – 1 – M5	15	10	M 5	12,5	
15 – 15 – 1 – M5	15	15	M 5	12,5	
20 – 08 – 1	20	8	M 6	18	
20 – 10 – 1	20	10	M 6	18	
20 – 15 – 1	20	15	M 6	18	
20 – 20 – 1	20	20	M 6	18	
20 – 25 – 1	20	25	M 6	18	
25 – 10 – 1	25	10	M 6	18	
25 – 15 – 1	25	15	M 6	18	
25 – 20 – 1	25	20	M 6	18	
25 – 25 – 1	25	25	M 6	18	



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

25 – 30 – 1	25	30	M 6	18
25 – 15 – 1 – M8	25	15	M 8	20
25 – 20 – 1 – M8	25	20	M 8	20
25 – 25 – 1 – M8	25	25	M 8	20
25 – 30 – 1 – M8	25	30	M 8	20
30 – 15 – 1	30	15	M 8	20
30 – 20 – 1	30	20	M 8	20
30 – 25 – 1	30	25	M 8	20
30 – 30 – 1	30	30	M 8	20
30 – 35 – 1	30	35	M 8	20
30 – 40 – 1	30	40	M 8	20
40 – 20 – 1	40	20	M 8	23
40 – 25 – 1	40	25	M 8	23
40 – 30 – 1	40	30	M 8	23
40 – 35 – 1	40	35	M 8	23
40 – 40 – 1	40	40	M 8	23
40 – 25 – 1 – M10	40	25	M 10	28
40 – 30 – 1 – M10	40	30	M 10	28
40 – 40 – 1 – M10	40	40	M 10	28
50 – 20 – 1	50	20	M 10	28
50 – 25 – 1	50	25	M 10	28
50 – 30 – 1	50	30	M 10	28
50 – 40 – 1	50	40	M 10	28
50 – 45 – 1	50	45	M 10	28
50 – 50 – 1	50	50	M 10	28
60 – 20 – 1	60	20	M 10	28
60 – 30 – 1	60	30	M 10	28
60 – 40 – 1	60	40	M 10	28
60 – 45 – 1	60	45	M 10	28
60 – 50 – 1	60	50	M 10	28
70 – 25 – 1	70	25	M 10	28
70 – 30 – 1	70	30	M 10	28
70 – 45 – 1	70	45	M 10	28
70 – 60 – 1	70	60	M 10	28
70 – 25 – 1 – M12	70	25	M 12	37
70 – 30 – 1 – M12	70	30	M 12	37
70 – 45 – 1 – M12	70	45	M 12	37



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

70 – 60 – 1 – M12	70	60	M 12	37
75 – 25 – 1	75	25	M 12	37
75 – 40 – 1	75	40	M 12	37
75 – 50 – 1	75	50	M 12	37
75 – 55 – 1	75	55	M 12	37
75 – 50 – 1 – M16	75	50	M 16	42
75 – 55 – 1 – M16	75	55	M 16	42
100 – 40 – 1	100	40	M 16	41
100 – 50 – 1	100	50	M 16	41
100 – 55 – 1	100	55	M 16	41
100 – 60 – 1	100	60	M 16	41
100 – 75 – 1	100	75	M 16	41
100 – 100 – 1	100	100	M 16	41
125 – 75 – 1	125	75	M 16	41
125 – 100 – 1	125	100	M 16	41
150 – 50 – 1	150	50	M 16	45
150 – 55 – 1	150	55	M 16	45
150 – 75 – 1	150	75	M 16	45
150 – 100 – 1	150	100	M 16	45
150 – 50 – 1 – M20	150	50	M 20	45
150 – 55 – 1 – M20	150	55	M 20	45
150 – 75 – 1 – M20	150	75	M 20	45
150 – 100 – 1 – M20	150	100	M 20	45
200 – 100 – 1	200	100	M 20	45