



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

Gummi-Metall-Puffer Ausführung 3


beidseitig Innengewinde

Shore A Härte 55° +/-5°

Metall-Werkstoff: Stahl

Oberfläche: Blau verzinkt 8-12 µ / RoHS konform

Toleranz: DIN ISO 3302-1 Klasse M 3



Artikel	Durchmesser D mm	Höhe H mm	Gewinde G	Gewindelänge L mm	Gewindetiefe T mm
10 – 15 – 3	10	15	M 4		5
15 – 15 – 3	15	15	M 4		5
15 – 20 – 3	15	20	M 4		5
15 – 25 – 3	15	25	M 4		5
15 – 15 – 3 – M5	15	15	M 5		5
20 – 20 – 3	20	20	M 6		6
20 – 25 – 3	20	25	M 6		6
25 – 20 – 3	25	20	M 6		6
25 – 25 – 3	25	25	M 6		6
25 – 30 – 3	25	30	M 6		6
25 – 35 – 3	25	35	M 6		6
25 – 25 – 3 – M8	25	25	M 8		7
25 – 30 – 3 – M8	25	30	M 8		7
30 – 20 – 3	30	20	M 8		8
30 – 25 – 3	30	25	M 8		8
30 – 30 – 3	30	30	M 8		8
30 – 35 – 3	30	35	M 8		8
30 – 40 – 3	30	40	M 8		8
40 – 30 – 3	40	30	M 8		8
40 – 35 – 3	40	35	M 8		8
40 – 40 – 3	40	40	M 8		8
40 – 30 – 3 – M10	40	30	M 10		10
40 – 35 – 3 – M10	40	35	M 10		10



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

40 – 40 – 3 – M10	40	40	M 10	10
50 – 30 – 3	50	30	M 10	10
50 – 40 – 3	50	40	M 10	10
50 – 45 – 3	50	45	M 10	10
50 – 50 – 3	50	50	M 10	10
60 – 30 – 3	60	30	M 10	10
60 – 40 – 3	60	40	M 10	10
60 – 45 – 3	60	45	M 10	10
60 – 50 – 3	60	50	M 10	10
70 – 45 – 3	70	45	M 10	10
70 – 60 – 3	70	60	M 10	10
70 – 45 – 3 – M12	70	45	M 12	12
70 – 60 – 3 – M12	70	60	M 12	12
75 – 40 – 3	75	40	M 12	12
75 – 50 – 3	75	50	M 12	12
75 – 55 – 3	75	55	M 12	12
75 – 50 – 3 – M16	75	50	M 16	16
75 – 55 – 3 – M16	75	55	M 16	16
100 – 40 – 3	100	40	M 16	16
100 – 50 – 3	100	50	M 16	16
100 – 55 – 3	100	55	M 16	16
100 – 60 – 3	100	60	M 16	16
100 – 75 – 3	100	75	M 16	16
100 – 100 – 3	100	100	M 16	16
125 – 75 – 3	125	75	M 16	16
125 – 100 – 3	125	100	M 16	16
150 – 50 – 3	150	50	M 16	16
150 – 55 – 3	150	55	M 16	16
150 – 75 – 3	150	75	M 16	16
150 – 100 – 3	150	100	M 16	16
150 – 50 – 3 – M20	150	50	M 20	20
150 – 55 – 3 – M20	150	55	M 20	20
150 – 75 – 3 – M20	150	75	M 20	20
150 – 100 – 3 – M20	150	100	M 20	20

Gummi · Kunststoffe
Dichtungstechnik
Schlauchtechnik
Industriebedarf



LUX & CO.

Bergwerks- und Industriebedarf GmbH

Lux & Co. GmbH · Postfach 520364 · 50952 Köln

200 – 100 – 3

200

100

M 20

20

