



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

Gummi-Metall-Puffer

Ausführung 4


einseitig Außengewinde

Shore A Härte 55° +/-5°

Metall-Werkstoff: Stahl

Oberfläche: Blau verzinkt 8-12 µ / RoHS konform

Toleranz: DIN ISO 3302-1 Klasse M 3



Artikel	Durchmesser D mm	Höhe H mm	Gewinde G	Gewindelänge L mm	Gewindetiefe T mm
08 – 06 – 4	8	6	M 3	6	
08 – 08 – 4	8	8	M 3	6	
10 – 05 – 4	10	5	M 4	10	
10 – 08 – 4	10	8	M 4	10	
10 – 10 – 4	10	10	M 4	10	
10 – 15 – 4	10	15	M 4	10	
12,5 – 12,5 – 4	12,5	12,5	M 5	12,5	
12,5 – 19 – 4	12,5	19	M 5	12,5	
15 – 07 – 4	15	7	M 4	10	
15 – 08 – 4	15	8	M 4	10	
15 – 10 – 4	15	10	M 4	10	
15 – 15 – 4	15	15	M 4	10	
15 – 20 – 4	15	20	M 4	10	
15 – 25 – 4	15	25	M 4	10	
15 – 10 – 4 – M5	15	10	M 5	12,5	
15 – 15 – 4 – M5	15	15	M 5	12,5	
20 – 04 – 4	20	4	M 6	18	
20 – 05 – 4	20	5	M 6	18	
20 – 08 – 4	20	8	M 6	18	
20 – 10 – 4	20	10	M 6	18	
20 – 11 – 4	20	11	M 6	18	
20 – 13,5 – 4	20	13,5	M 6	18	
20 – 15 – 4	20	15	M 6	18	
20 – 20 – 4	20	20	M 6	18	
20 – 25 – 4	20	25	M 6	18	



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

25 – 10 – 4	25	10	M 6	18
25 – 13 – 4	25	13	M 6	18
25 – 15 – 4	25	15	M 6	18
25 – 17 – 4	25	17	M 6	18
25 – 20 – 4	25	20	M 6	18
25 – 25 – 4	25	25	M 6	18
25 – 30 – 4	25	30	M 6	18
25 – 10 – 4 – M8	25	10	M 8	20
25 – 15 – 4 – M8	25	15	M 8	20
25 – 20 – 4 – M8	25	20	M 8	20
25 – 25 – 4 – M8	25	25	M 8	20
25 – 30 – 4 – M8	25	30	M 8	20
30 – 08 – 4	30	8	M 8	20
30 – 10 – 4	30	10	M 8	20
30 – 15 – 4	30	15	M 8	20
30 – 17 – 4	30	17	M 8	20
30 – 20 – 4	30	20	M 8	20
30 – 25 – 4	30	25	M 8	20
30 – 28 – 4	30	28	M 8	20
30 – 30 – 4	30	30	M 8	20
30 – 35 – 4	30	35	M 8	20
30 – 40 – 4	30	40	M 8	20
40 – 20 – 4	40	20	M 8	23
40 – 25 – 4	40	25	M 8	23
40 – 30 – 4	40	30	M 8	23
40 – 35 – 4	40	35	M 8	23
40 – 40 – 4	40	40	M 8	23
40 – 20 – 4 – M10	40	20	M 10	28
40 – 25 – 4 – M10	40	25	M 10	28
40 – 30 – 4 – M10	40	30	M 10	28
40 – 35 – 4 – M10	40	35	M 10	28
40 – 40 – 4 – M10	40	40	M 10	28
50 – 20 – 4	50	20	M 10	28
50 – 25 – 4	50	25	M 10	28
50 – 30 – 4	50	30	M 10	28
50 – 40 – 4	50	40	M 10	28
50 – 45 – 4	50	45	M 10	28
50 – 50 – 4	50	50	M 10	28



Lux & Co. GmbH · Postfach 520364 · 50952 Köln

60 – 20 – 4	60	20	M 10	28
60 – 25 – 4	60	25	M 10	28
60 – 30 – 4	60	30	M 10	28
60 – 45 – 4	60	45	M 10	28
60 – 50 – 4	60	50	M 10	28
70 – 25 – 4	70	25	M 10	28
70 – 30 – 4	70	30	M 10	28
70 – 45 – 4	70	45	M 10	28
70 – 60 – 4	70	60	M 10	28
70 – 25 – 4 – M12	70	25	M 12	37
70 – 30 – 4 – M12	70	30	M 12	37
70 – 45 – 4 – M12	70	45	M 12	37
70 – 60 – 4 – M12	70	60	M 12	37
75 – 25 – 4	75	25	M 12	37
75 – 40 – 4	75	40	M 12	37
75 – 50 – 4	75	50	M 12	37
75 – 55 – 4	75	55	M 12	37
75 – 40 – 4 – M16	75	40	M 16	42
75 – 50 – 4 – M16	75	50	M 16	42
75 – 55 – 4 – M16	75	55	M 16	42
100 – 40 – 4	100	40	M 16	41
100 – 50 – 4	100	50	M 16	41
100 – 55 – 4	100	55	M 16	41
100 – 60 – 4	100	60	M 16	41
100 – 75 – 4	100	75	M 16	41
100 – 100 – 4	100	100	M 16	41
125 – 75 – 4	125	75	M 16	41
125 – 100 – 4	125	100	M 16	41
150 – 50 – 4	150	50	M 16	45
150 – 55 – 4	150	55	M 16	45
150 – 60 – 4	150	60	M 16	45
150 – 75 – 4	150	75	M 16	45
150 – 100 – 4	150	100	M 16	45
150 – 50 – 4 – M20	150	50	M 20	45
150 – 55 – 4 – M20	150	55	M 20	45
150 – 60 – 4 – M20	150	60	M 20	45
150 – 75 – 4 – M20	150	75	M 20	45

Gummi · Kunststoffe
Dichtungstechnik
Schlauchtechnik
Industriebedarf



LUX & CO.

Bergwerks- und Industriebedarf GmbH

Lux & Co. GmbH · Postfach 520364 · 50952 Köln

150 – 100 – 4 – M20	150	100	M 20	45
200 – 100 – 4	200	100	M 20	45
250 – 45 – 4	250	45	M 16	40